

Application No.: 09/821,428

Docket No.: JCLA5383-R

In The Claims:

Please amend the claims as follows:

Claim 1. (Currently Amended) A switch controller inside a switch device capable of easing network congestion, the switch controller has a plurality of ports and the switch device further includes a shared buffer and a plurality of physical layer devices (PHY), the shared buffer can be divided into a plurality of buffering units, the switch controller comprising:

a buffer control device coupled to the shared buffer for assigning and releasing the buffering units;

a plurality of port control devices coupled to the physical layer devices and the buffer control device, wherein each port control device has a one-to-one correspondence with the ports, the port control device that corresponds to a source port receives a network packet and then sends the packet to at least one of the buffering unit(s) for storage;

a forwarding control device coupled to the port control devices, and a target port of the packet is determined according to a header of the network packet; and

a queue control device coupled to the port control devices and the buffer control device, wherein the queue control device further includes a plurality of output queues, each output queue has a one-to-one correspondence with the port control devices, and the buffering unit for storing the packets is linked to the output queue corresponding to the port control device at a target port;

wherein each output port has a number of reserved buffering units which are not used by any other output port, and the source port triggers or terminates a congestion mode to control the

Application No.: 09/821,428

Docket No.: JCLA5383-R

number of free buffering units in response to the number of reserved buffering units in the output queue, and each port control device includes:

a receive medium access control device coupled to one of the physical layer devices, wherein the received medium access control device inspects any incoming network packet for errors, if no errors is found, the packet is accepted, otherwise the packet is returned;

a receive control device coupled to the receive medium access control device, the queue control device and the buffer control device, the receive control device issues requests to the buffer control device to assign at least one buffering units(s) for storing the packet and signals the queue control device to request queuing to the corresponding output queue;

an output control device, coupled to the queue control device and the buffer control device for outputting the packet from the output queue, and releasing the buffering units after the buffer control unit has sent out the packet;

a transmission medium access control device coupled to the output control device and one of the physical layer devices for outputting the packet to the physical layer device, and when the congestion control mode is triggered, the transmission medium access control device within the port control device that corresponds to the source port sends out a control signal to execute the congestion control operation; and

a physical layer control device coupled to the transmission medium access control device and one of the physical layer devices, receiving a plurality of state signals from an external network device to select a proper congestion control mode.

Application No.: 09/821,428

Docket No.: JCLA5383-R

Claim 2. (Previously Presented) The switch controller of claim 1, wherein a k^{th} port is the target port and a plurality of parameters are defined as follows:

$Q[k]$: length of the output queue of the k^{th} port;

R_{max} : number of maximum buffering units reserved for each port;

$R[k]$: number of buffering units reserved for the k^{th} port,

$R[k] = 0$ when $R_{\text{max}} \leq Q[k]$; and

$R[k] = R_{\text{max}} - Q[k]$ when $R_{\text{max}} > Q[k]$.

Ψ : the total number of reserved buffering units, i.e., $\Psi = \sum_{k=0}^n R[k]$;

Φ : number of free buffering units;

C : the number of reserved buffering units in a virtual free space;

Ω : number of virtual free buffers,

when $\Phi \leq C$, $\Omega = 0$, and when $\Phi > C$, $\Omega = \Phi - C$;

W : minimum number of reserved virtual buffering unit;

wherein the congestion control mode is triggered when $\Omega \leq \max \{ \Psi, W \}$ and

$R[k] = 0$.

Claim 3. (Original) The switch controller of claim 2, wherein the number of reserved buffering unit in virtual free space C is 10, and the lowest number of reserved buffering units in virtual free space W is 28.

Application No.: 09/821,428

Docket No.: JCLA5383-R

Claim 4. (Original) The switch controller of claim 1, wherein a k^{th} port is the target port and a plurality of parameters are defined as follows:

$Q[k]$: the output queue length of the k^{th} port;

R_{max} : the greatest number of buffering units reserved by the port;

$R[k]$: the number of buffering units reserved by the k^{th} port,

when $R_{\text{max}} \leq Q[k]$, $R[k] = 0$, and

when $R_{\text{max}} > Q[k]$, $R[k] = R_{\text{max}} - Q[k]$;

wherein the congestion control mode for the k^{th} port is triggered when any of the other ports has already triggered a congestion control mode and $R[k] = 0$.

Claim 5. (Cancelled)

Claim 6. (Currently Amended) The switch controller of [[claim 5]] claim 1, wherein the controller further includes a CPU port capable of connecting with a CPU for a two-way data transmission via an ISA/IDE interface.

Claim 7. (Currently Amended) The switch controller of [[claim 5]] claim 1, wherein the congestion control mode includes a backpressure control mode, a drop control mode and a flow control mode.

Application No.: 09/821,428

Docket No.: JCLA5383-R

Claim 8. (Original) The switch controller of claim 7, wherein the backpressure control mode is selected when the external network device operates in a half-duplex mode without flow control capability.

Claim 9. (Original) The switch controller of claim 7, wherein the drop control mode is selected when the external network device operates in a full-duplex mode but without flow control capability.

Claim 10. (Original) The switch controller of claim 7, wherein the flow control mode is selected when the external network device operates in a full-duplex mode with flow control capability.

Claim 11. (Currently Amended) A method for easing data transmission congestion in a switch device having a plurality of ports, the switch device includes a shared buffer capable of dividing into a plurality of buffering units, comprising the steps of:

providing a plurality of output queues, wherein the output queues have a one-to-one correspondence with the ports;

assigning the buffering units in the shared buffer;

receiving a packet from a source port and storing the packet in an assigned buffering unit;

determining the target port of a network packet according to a header of the packet;

Application No.: 09/821,428

Docket No.: JCLA5383-R

linking buffering unit containing the stored network packet to the output queue that corresponds to the target port; [[and]]

outputting the network packet from the target port;

releasing the buffering unit after the network packet is output;

selecting a type of congestion control in response to an external network device; and

controlling free buffering units according to a number of reserved buffering units in the output queue and a triggering or a terminating condition of the source port;

wherein each output port has a number of reserved buffering units which are not used by any other output port, and the congestion control mode includes a backpressure control mode, a drop control mode and a flow control mode.

Claim 12. (Previously Presented) The method of claim 11, wherein a k^{th} port is the target port and a plurality of parameters are defined as follows:

$Q[k]$: length of the output queue of the k^{th} port;

R_{max} : number of maximum buffering units reserved for each port;

$R[k]$: number of buffering units reserved for the k^{th} port,

$R[k] = 0$ when $R_{\text{max}} \leq Q[k]$; and

$R[k] = R_{\text{max}} - Q[k]$ when $R_{\text{max}} > Q[k]$

Ψ : the total number of reserved buffering units, i.e., $\Psi = \sum_{k=0}^n R[k]$;

Φ : number of free buffering units;

Application No.: 09/821,428

Docket No.: JCLA5383-R

C : number of reserved buffering units in a virtual free space;

Ω : number of virtual free buffers,

when $\Phi \leq C$, $\Omega = 0$, and when $\Phi > C$, $\Omega = \Phi - C$;

W : minimum number of reserved virtual buffering unit;

wherein a congestion control mode is triggered when $\Omega \leq \max \{ \Psi, W \}$ and $R[k] = 0$.

Claim 13. (Original) The method of claim 12, wherein the number of reserved buffering unit in virtual free space C is 10, and the minimum number of reserved buffering units in virtual free space W is 28.

Claim 14. (Original) The method of claim 11, wherein a k^{th} port is the target port and a plurality of parameters are defined as follows:

$Q[k]$: length of the output queue of the k^{th} port;

R_{\max} : number of maximum buffering units reserved by the port;

$R[k]$: number of buffering units reserved by the k^{th} port,

$R[k] = 0$ when $R_{\max} \leq Q[k]$; and

$R[k] = R_{\max} - Q[k]$ when $R_{\max} > Q[k]$;

wherein a congestion control mode is triggered when any one of the port has already triggered a congestion control mode and $R[k] = 0$.

Application No.: 09/821,428

Docket No.: JCLA5383-R

Claim 15. (Previously Presented) The method of claim 11, wherein a plurality of parameters are defined as follows:

Φ : the number of free (unassigned) buffering units;

C : the number of reserved buffering units in a virtual free space;

Ω : the number of virtual free buffers,

when $\Phi \leq C$, $\Omega = 0$, and when $\Phi > C$, $\Omega = \Phi - C$;

when $\Phi = 0$, the congestion control mode is triggered.

Claim 16-17 (Cancelled)

Claim 18. (Currently Amended) The method of [[claim 17]] claim 11, wherein backpressure control mode is selected when the external network device operates in a half-duplex mode without flow control capability.

Claim 19. (Currently Amended) The method of [[claim 17]] claim 11, wherein the drop control mode is selected when the external network device operates in a full-duplex mode but without flow control capability.

Claim 20. (Currently Amended) The method of [[claim 17]] claim 11, wherein the flow control mode is selected when the external network device operates in a full-duplex mode with flow control capability.